


Axial play adjustment when mounting bearings



Optimize your entire process  chain with flexible shims

Flexible fitting elements



LAMINUM[®]

Laminum[®] "laminated"

- Peelable
- Sealing capacity
- From 0.01 mm
- Simple handling
- Simple thickness measurement



LAMIVARIO[®]

Lamivario[®] "edge-welded"

- Manually detachable
- Foils are reusable
- Foil thickness range from 0.005 mm
- Fast and safe handling
- High temperatures


Massive shims



LAMISOL[®]

Lamisol[®] "solid"


- For all mechanical loads
- Temperatures > 200°C
- Single foil thicknesses from 0.005 mm to 10 mm
- One-off production or assortments in special packaging and EDI



Construction Advice

The placement of the fitting rings is important under consideration of the material structure and anticipated operating loads.

We would be pleased to advise you and can also prepare samples for you on the basis of your drawings. One-off and series production are among the demands we face every day.



Your advantages:

- ➔ Shims based on your drawings with process and material consultancy
- ➔ For fast and efficient assembly
- ➔ To reduce costs in your process-chain

We would be pleased to advise you in person:

Tel. +49 6074-40 99 80 or **vertrieb@georg-martin.de**

We are looking forward to your visit!

Georg Martin GmbH – laminated shims since 1956.

Georg Martin GmbH
Martinstrasse 55
63128 Dietzenbach
Germany

designed,
engineered &
made in Germany

AS9100:D
ISO 9001
ISO 14001

